



GD50 shown minus hose whips, in-line valve and couplers

SPECIFICATIONS

| ITEM | U.S.A. | METRIC |
|----------------------|--|------------------|
| CAPACITY (GD50132RF) | 1/2 and 5/8 in. Rod | 12 and 16 mm Rod |
| CAPACITY (GD50133) | 3/4 and 1 in. Rod | 19 and 25 mm Rod |
| FLOW RANGE | 5 - 9 gpm | 19 - 34 lpm |
| PRESSURE | 1500 - 2000 psi | 105 - 140 bar |
| PORTS | -8 SAE Straight Thread O-Ring | |
| SYSTEM TYPE | Open Center/Closed Center | |
| WEIGHT | 52 lbs | 24 kg |
| LENGTH | 25.5 in. | 64.8 mm |
| CONNECTION | 3/8 in. Flush-Face Quick Disconnect Couplers | |
| HOSE WHIPS | Yes | |

Features and Benefits

The Stanley GD50 Ground Rod Driver provides a competitive means of driving rods with proven, hard-hitting technology.

Two models are available, the GD50132RF that drives 1/2-inch and 5/8-inch rods the GD50133 that drives 3/4-inch and 1-inch rods.

The lifting eye allows the operator to suspend the driver above the rod with ease. The long side handles give the operator control during the driving process.

The in-line valve in the 8-foot hose whips gives the operator On/Off control where he is standing.

Both GD50 models have driving anvils which are designed to fit the rods which helps to minimize damage to the rod ends. The anvil which remains in contact with the rod while the hammer in the ground rod driver delivers its high-energy blows to the anvil. The deep socket of the anvil keeps the driver from jumping off the end of the rod.

The anvils are interchangeable, so that you can change the capacity of a ground rod driver by simply changing anvils. The removal of two bolts is all that is required to service the front end of the GD50.

ORDERING INFORMATION

| MODEL | PART NO. | DESCRIPTION |
|-------|-----------|--------------------------------|
| GD50 | GD50132RF | Side Handle, 1/2 - 5/8 in. Rod |
| GD50 | GD50133RF | Side Handle, 3/4 - 1 in. Rod |

Note: Above models include two each hose whips with in-line valve, flush-face couplers and 8 ft hose whips.

WARRANTY

Stanley Hydraulic Tools and their associated parts are warranted against defects in materials and workmanship for a period of twelve months from the date of purchase. Stanley Hydraulic Tools reserves the right to repair or replace only those parts which prove to have been defective at the time of purchase. This warranty becomes void if maximum flow and pressure ratings are exceeded.

All Stanley Hydraulic Tools, parts, accessories and allied equipment are subject to design improvements, specification and price changes at any time without notice and with no obligation to units already sold. Weights, dimensions and operating specifications listed herein are subject to change without notice. Where specifications are critical to your applications, please consult Stanley Hydraulic Tools.

Steffen Inc
623 W 7th Street
Sioux City, IA 51103
Toll Free: 800-382-3599
Fax: 712-279-8070
Email: stanley-sales@steffeninc.com

STANLEY[®]