

BR45S



Features and Benefits

Rugged, Lightweight and Powerful construction of the **BR45** T handle and **BR45S** anti-vibration handle breakers make them ideal for use in the 35-65 pound class. Designed for light- to medium-duty operation, they excel at curb and sidewalk demolition, asphalt cutting, and are popular for ground rod driving with electric utilities.

The Stanley Easi-Ride™ foot, offered on the **BR45** absorbs and controls tool-bit bounce, greatly reducing operator fatigue.

Spring-Isolated, Anti-Vibration Handles (**BR45S**) reduce operator fatigue, literally allowing the breaker to float in the user's hands.

SPECIFICATIONS

ITEM	U.S.A.	METRIC
OUTPUT	1800 Blows Per Minute	
INPUT FLOW RANGE	7 - 9 gpm	26 - 34 lpm
INPUT PRESSURE	1500 - 2000 psi	105 - 140 bar
MAX. BACK PRESSURE	250 psi	17 bar
OPTIMUM FLOW	8 gpm	30 lpm
PORTING	8 SAE O-Ring	
CONNECTOR	3/8 in. Male Pipe Hose End	

BR45 (T Handle)

STEEL CAPACITY	4-1/4 x 1 in. Hex*, 6 x 1-1/8 Hex & 6 x 1-1/4 in. Hex	
WEIGHT	45/48 lbs.	20/21 kg
LENGTH	23.5/25.5 in.	60/65 cm
WIDTH (at handles)	14 in.	35 cm

BR45S (Anti-Vibration Handle)

STEEL CAPACITY	6 x 1-1/8 in. Hex & 6 x 1-1/4 in. Hex	
WEIGHT	48/51 lbs.	22/23 kg
LENGTH	25.2/28.25 in.	65/72 cm
WIDTH (at handles)	17.5 in.	44.5 cm

* Not available with Easi-Ride™ foot.

Built in Handle Stops on anti-vibration handle model (**BR45S**) allow operator to apply full body weight in tough applications.

Feathering On/Off Valve allows the operator to control the output energy of the tool through the full range from 0 to 1,800 blows per minute, making startup and initial tool placement easy.

Diaphragm-Type Accumulator design provides for ease of maintenance and extended service life of the tool. All models operate at a maximum back pressure of 250 psi (17 bar) on open-center systems.

Complete Line of Steels for breaking, cutting, or driving are available directly from your Stanley dealer.

Underwater Models Available.

MODEL NUMBERS

MODEL	DESCRIPTION
BR45150	BR45 T-Handle Breaker, 1 in. Hex
BR45120E	BR45 T-Handle Breaker, 1-1/8 in. Hex, Easi-Ride Foot
BR45130E	BR45 T-Handle Breaker, 1-1/4 in. Hex, Easi-Ride Foot
BR45125S	BR45S Anti-Vibration Handle Breaker, 1-1/8 in. Hex
BR45135S	BR45S Anti-Vibration Handle Breaker, 1-1/4 in. Hex
BR45350	BR45 Underwater T-Handle Breaker, 1 in. Hex

Note: All models listed above ship with hose whips.

ACCESSORIES

PART NO.	DESCRIPTION
07702	Moil Point, 14 in. (35.6 cm)*
07703	Narrow Chisel, 14 in. (35.6 cm)*
07704	Chisel, 3 in. (76 mm) blade x 14 in. (35.6 cm)*
07705	Clay Spade, 5-1/2 in. (14 cm) blade
07706	Asphalt Wedge, 3 in. (76 mm) blade
07707	Ground Rod Driver, 1 in. (25 mm) rod
14931	Digging Chisel
02331	Clay Spade, 5-1/2 in. (14 cm) blade
02332	Asphalt Cutter, 5 in. (12.7 cm) blade x 11 in. (28 cm)*
02333	Moil Point, 14 in. (35.6 cm)*
02334	Chisel, 3 in. (76 mm) blade x 14 in. (35.6 cm)*
03990	Chisel Point, 14 in. (35.6 cm)*
04176	Ground Rod Driver, 1 in. (25 mm) rod
08106	Asphalt Wedge, 12 in. (30.5 cm)*
08107	Keen Kut, 16 in. (40.6 cm)*
02335	Asphalt Cutter, 5 in. (12.7 cm) blade x 11 in. (28 cm)*
02336	Moil Point, 14 in. (35.6 cm)*
02337	Chisel, 3 in. (76mm) blade x 14 in. (35.6 cm)*
02338	Heavy Duty Chisel, 1 in. (25 mm) x 14 in. (35.6 cm)*
04367	Ground Rod Driver, 1 in. (25 mm) rod
04404	Heavy Duty Moil Point, 18 in. (45.7 cm)*
04405	Clay Spade, 8 in. (20.3 cm) blade
08118	Brick Wedge
18119	Asphalt Wedge
09262	Clay Spade, 5-1/2 in. (14 cm)
17782	Detachable Shank (requires no. 17783)
17783	Tamping Pad, 6 in. (15.2 cm) pad (requires no. 17782)

* Length measured from bottom tip of tool to bottom surface of collar.

All Stanley Hydraulic Tools, Parts, Accessories and allied equipment are subject to design improvements, specification and price changes at any time without notice and with no obligation to units already sold. Weights, dimensions and operating specifications listed herein are subject to change without notice. Where specifications are critical to your application, please consult Stanley Hydraulic Tools.

Call the Stanley Hydraulic Tools dealer nearest you...

WARRANTY

Stanley Hydraulic Tools and their associated parts are warranted against defects in materials and workmanship for a period of twelve months from the date of purchase. Stanley Hydraulic Tools reserves the right to repair or replace only those parts which prove to have been defective at the time of purchase. This warranty becomes void if maximum flow and pressure ratings are exceeded.

TEST EQUIPMENT

PART NO.	DESCRIPTION
02835	Accumulator Tester
03189	20 gpm (75 lpm) Flow Meter
04182	Flow and Pressure Tester
31254	Accumulator Charge Kit

SERVICE TOOLS

PART NO.	DESCRIPTION
01120	Tamper Sleeve Tool
04595	Seal Kit
04919	Flow Sleeve Removal Tool
05640	Accumulator Cylinder Puller
04910	Flow Sleeve Removal Tube
04337	O-Ring Tool Kit



STANLEY

Steffen Inc
623 W 7th Street
Sioux City, IA 51103
Toll Free: 800-382-3599
Fax: 712-279-8070
Email: stanley-sales@steffeninc.com