

BR37 - BR40



BR37



BR40

OPERATION AND PERFORMANCE

ITEM	BR37		BR40	
	U.S.A.	METRIC	U.S.A.	METRIC
Capacity	3 3/4 x 7/8 in Hex	8.2 x 2.2 cm	4 1/4 x 1 in Hex	10.8 x 2.5 cm
Weight	37 lb	17 kg	41 lb	18.6 kg
Length	22 1/2 in	57 cm	23 1/2 in	60 cm
Width	14 in	36 cm	14 in	36 cm
Pressure	1500-2000 psi	105-140 bar	1300-2000 psi	90-140 bar
Flow Range	7-9 gpm	26-34 lpm	4-6 gpm	15-23 lpm
Optimum Flow	8 gpm	30 lpm	5 gpm	20 lpm
Porting	8 SAE O-Ring			
Hose Whips	Yes			
Connect Size and Type	3/8 in Male Pipe Hose End			

Stanley's line of hand-held breakers is the largest in the world. Breakers are available for any application.

They can be used for light to heavy concrete demolition, driving of posts, pole anchors and asphalt cutting.

They feature a trouble free diaphragm accumulator and can handle system backpressures of up to 250 psi/17 bar. A handy feature on these breakers is a feathering valve to make start-up and initial placement of the steel easy.

The **BR37** is a lightweight breaker well suited for breaking sidewalk and curbing, asphalt cutting and driving rods.

Its handy size and lightweight construction make it particularly useful for use as a digger in trench work where horizontal operation is required.

The **BR40** is the ideal breaker for light applications where noise and economy of operation are prime concerns.

The **BR40** has been designed to run from the Stanley HP08 power unit or dual circuit HPR compact. Requiring only 5 gpm of hydraulic flow, the **BR40** and HP08 make-up a total breaker package weighing slightly more than 200 lbs – an ideal combination for rental yard use and light construction applications.

**ACCESSORIES**

PART NO.	DESCRIPTION
<b>BR37</b>	
02328	Clay Spade 16 in/40.6 cm U/C*
02330	3 in/7.6 cm Chisel, 14 in/35.6 cm U/C*
02339	1 in/2.5 cm Chisel, 14 in/35.6 cm U/C*
02340	Digging Chisel 3 x 10 in/7.6 x 25.4 cm Blade by 17 1/4 in/43.8 cm U/C*
02341	Asphalt Cutters 5 in/12.7 cm Blade x 11 in/27.9 cm U/C*
04401	Moil Point, 18 in/45.7 cm U/C*
04402	3 in/7.6 cm Chisel, 18 in/45.7 cm U/C*
04403	Concrete Buster, 14 in/35.6 cm U/C*
04961	Moil Point, 14 in/35.6 cm U/C*
05255	Rod Driver, 3/4 in/1.9 cm
<b>BR40</b>	
07702	Moil Point, 14 in/35.6 cm U/C*
07703	Narrow Chisel Point, 14 in/35.6 cm U/C*
07704	3 in/7.6 cm Chisel, 14 in/35.6 cm U/C*
07705	Clay spade, 5 1/2 in/14 cm Blade
07706	Asphalt Wedge, 3 in/7.6 cm wide
07707	Ground Rod Driver, 1 in/2.5 cm

*\*U/C Denotes Under Collar*

**WARRANTY**

Stanley Hydraulic Tools and their associated parts are warranted against defects in materials and workmanship for a period of twelve months from the date of purchase. Stanley Hydraulic Tools reserves the right to repair or replace only those parts which prove to have been defective at the time of purchase. This warranty becomes void if maximum flow and pressure ratings are exceeded.

**ORDERING INFORMATION**

PART NO.	DESCRIPTION	CAPACITY
BR37110	Open Center	7/8 in Hex
BR40550	Open Center	1 in Hex

All Stanley Hydraulic Tools, Parts, Accessories and allied equipment are subject to design improvements, specification and price changes at any time without notice and with no obligation to units already sold. Weights, dimensions and operating specifications listed herein are subject to change without notice. Where specifications are critical to your application, please consult Stanley Hydraulic Tools.

Call the Stanley Hydraulic Tools dealer nearest you...

**Stanley  
Hydraulic Tools**

**STANLEY**

Steffen Inc  
623 W 7th Street  
Sioux City, IA 51103  
Toll Free: 800-382-3599  
Fax: 712-279-8070  
Email: stanley-sales@steffeninc.com