

BR72



BR72S



SPECIFICATIONS

ITEM	U.S.A.	METRIC
OUTPUT	1700 Blows Per Minute	
INPUT FLOW RANGE	7 - 9 gpm	26 - 34 lpm
INPUT PRESSURE	1500 - 2000 psi	105 - 140 bar
MAX. BACK PRESSURE	250 psi	17 bar
OPTIMUM FLOW	8 gpm	30 lpm
STEEL CAPACITY	6 (15.2 cm) x 1-1/8 Hex & 6 (15.2 cm) x 1-1/4 in Hex	
PORTING	8 SAE O-Ring	
CONNECTOR	3/8 in Male Pipe Hose End	
BR72		
WEIGHT	59 lbs.	27 kg
LENGTH	28 in	71 cm
WIDTH (at handles)	14.25 in	36 cm
BR72S		
WEIGHT	61 lbs.	27.6 kg
LENGTH	29.5 in	75 cm
WIDTH (at handles)	17.5 in	44.5 cm

Stanley's line of handheld breakers is the largest in the world, with a wide selection of models suited to virtually any application.

The **BR72** and **BR72S** are medium- to heavy-duty tools for work in the 70 pound class. They are highly productive in utility construction, street maintenance, repair of water and gas mains, and general contracting jobs.

Spring-Dampened, Anti-Vibration

Handles (**BR72S**) reduce operator fatigue, literally allowing the breaker to float in the user's hands.

Built in Handle Stops on anti-vibration handle model (**BR72S**) allow operator to apply full body weight in tough applications.

Feathering On/Off Valve controls speed, making startup and initial tool placement easy.

Makes Conversion Easy to hydraulic tools. The **BR72S** uses the same style foot found on many air breakers, giving the "ride and feel" of a pneumatic tool.

Complete Line of Steels for breaking, cutting or driving available from Stanley Hydraulic Tools.

ACCESSORIES

PART NO.	DESCRIPTION
	1-1/4 in Hex x 6 in Shank
02331	Clay Spade, 5-1/2 in (14 cm) blade
02332	Asphalt Cutter, 5 in (12.7 cm) blade x 11 in (28 cm)*
02333	Moil Point, 14 in (35.6 cm)*
02334	Chisel, 3 in (76 mm) blade x 14 in (35.6 cm)*
03990	Chisel Point, 14 in (35.6 cm)*
04176	Ground Rod Driver, 1 in (25 mm) rod
08106	Asphalt Wedge, 12 in (30.5 cm)*
	1-1/8 in Hex x 6 in Shank
02335	Asphalt Cutter, 5 in (12.7 cm) blade x 11 in (28 cm)*
02336	Moil Point, 14 in (35.6 cm)*
02337	Chisel, 3 in (76mm) blade x 14 in (35.6 cm)*
02338	Heavy Duty Chisel, 1 in (25 mm) x 14 in (35.6 cm)*
04367	Ground Rod Driver, 1 in (25 mm) rod
04404	Heavy Duty Moil Point, 18 in (45.7 cm)*
04405	Clay Spade, 8 in (20.3 cm) blade
08119	Asphalt Wedge
09262	Clay Spade, 5-1/2 in (14 cm)
17782	Detachable Shank (requires no. 17783)
17783	Tamping Pad, 6 in (15.2 cm) pad (requires no. 17782)

* Length measured from bottom tip of tool to bottom surface of collar.

WARRANTY

Stanley Hydraulic Tools and their associated parts are warranted against defects in materials and workmanship for a period of twelve months from the date of purchase. Stanley Hydraulic Tools reserves the right to repair or replace only those parts which prove to have been defective at the time of purchase. This warranty becomes void if maximum flow and pressure ratings are exceeded.

ORDERING INFORMATION

PART NO.	DESCRIPTION
BR72120	BR72 T-Handle Breaker, 1-1/8 in Hex
BR72125S	BR72S Anti-Vibration Handle Breaker, 1-1/8 in Hex
BR72130	BR72 T-Handle Breaker, 1-1/4 in Hex
BR72135S	BR72S Anti-Vibration Handle Breaker, 1-1/4 in Hex

All Stanley Hydraulic Tools, Parts, Accessories and allied equipment are subject to design improvements, specification and price changes at any time without notice and with no obligation to units already sold. Weights, dimensions and operating specifications listed herein are subject to change without notice. Where specifications are critical to your application, please consult Stanley Hydraulic Tools.

Call the Stanley Hydraulic Tools dealer nearest you...

Stanley Hydraulic Tools

STANLEY[®]

Steffen Inc
623 W 7th Street
Sioux City, IA 51103
Toll Free: 800-382-3599
Fax: 712-279-8070
Email: stanley-sales@steffeninc.com